

GEORGIAN™

Square Lay-in & Tegular

medium texture



GEORGIAN Beveled Tegular with PRELUDE 15/16" Exposed Tee grid

Recycled Content: 39-46%, Fire Guard 49%

Contact TechLineSM for LEED Information. 1-877-ARMSTRONG

LEED Credits						
Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Low-Emitting Materials	Daylight & Views
✓	✓	✓	✓	✓	✓	✓

Key Selection Attributes



- Unique painted visual
- Durable
 - Washable
 - Impact-resistant
 - Scratch-resistant

30-Year System Performance Guarantee

Against Visible Sag
HumiGuard® Plus
(excludes item 791)



Against Mold/Mildew & Bacterial Growth
BioBlock™ Plus
(excludes item 791)

- Economical
- Good sound absorption

Typical Applications

- Offices
- Schools closed for summer
- Classrooms
- Corridors
- Auditoriums
- Many types of commercial interiors

Color



White (WH)

Visual Selection

Performance Selection



Dots represent highest level of performance.

Grid Face	Edge Profile	Item Number	Dimensions	UL Classified Acoustics		Fire Resist	Light Reflect	Sag Resist	Anti-Microbial	VOC Formaldehyde	Recycling Program	Durable			
				NRC	CAC							Wash	Impact	Scratch	
GEORGIAN															
9/16"	Beveled Tegular	1753	2' x 2' x 5/8"		0.55	35♦	Class A	0.86	HumiGuard+	BioBlock+	Low	Yes	Wash	Impact	Scratch
15/16"	Square Lay-in	764	2' x 2' x 5/8"		0.55	33	Class A	0.86	HumiGuard+	BioBlock+	Low	Yes	Wash	Impact	Scratch
		763	2' x 4' x 5/8"		0.55	33	Class A	0.86	HumiGuard+	BioBlock+	Low	Yes	Wash	Impact	Scratch
		898	2' x 4' x 5/8"		0.55	35	Fire Guard	0.86	HumiGuard+	BioBlock+	Low	Yes	Wash	Impact	Scratch
	791	30" x 5' x 3/4"		0.55	33	Class A	0.86	Standard	-	Low	Yes	Wash	Impact	Scratch	
	Beveled Tegular	1752	2' x 2' x 5/8"		0.55	35	Class A	0.86	HumiGuard+	BioBlock+	Low	Yes	Wash	Impact	Scratch

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

Class A: Flame Spread 25 or under

(UL Labeled) per ASTM E 1264

Fire Guard: A fire resistive ceiling when

used in applicable UL assemblies

ASTM E 1264 Classification

Type III, Form 2, Pattern C E

Sag Resistance

HumiGuard Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

Low Formaldehyde

Low Formaldehyde – contributing less than 13.5 ppb in typical conditions per ASHRAE Standard 62, "Ventilation for Acceptable Indoor Air Quality," California Code Title 24, and other building types in CHPS Section 1350.

Anti Mold/Mildew & Bacteria

BioBlock Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor - 1.6 (BTU units)

R Factor - 0.28 (Watts units)

Backloading Recommendation

Contact TechLine for specific information

Weight; Square Feet/Carton

See product details at armstrong.com/ceilings

30-Year Performance Guarantee and Warranty Information

See warranty details at armstrong.com/ceilings

Recommended Suspension System

Items	Suspension System
1753	9/16" TRIMLOK® Screw-Slot 9/16" SILHOUETTE® Bolt-Slot
763, 764, 791	15/16" PRELUDE®
1752	15/16" PRELUDE
898	15/16" PRELUDE XL Fire Guard

Also Compatible With

- 1753 ♦ 9/16" SUPRAFINE™
- CAC 33 9/16" SONATA™
- 9/16" INTERLUDE® XL

TechLineSM / 1 877 ARMSTRONG
1 877 276 7876

armstrong.com/ceilings (search: georgian)

CS-3031-207 © AWI Licensing Company, 2007

Printed in the United States of America • 10% post consumer waste. Printed with vegetable inks. Recyclable.

